

DE1-10

Taps and splitters



Vertical 1-way shunt with 10dB attenuation and F connector in TV and Satellite band(5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- **Die-cast and nickel-plated**, it ensures high performance, with very low insertion loss, high return loss and insulation.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the feed-through output and the input.**

DE1-10		
Code		280710
Taps		1
Insertion loss		
RC 5-40MHz	dB	1.5
TV 47-862MHz	dB	1.3
SAT 950-1750MHz	dB	1.6
SAT 1750-2150MHz	dB	2
SAT 2150-2400MHz	dB	2
Tap loss		
RC 5-40MHz	dB	10.5
TV 47-862MHz	dB	10.5
SAT 950-1750MHz	dB	11
SAT 1750-2150MHz	dB	11
SAT 2150-2400MHz	dB	11
Outputs Isolation		
RC 5-40MHz	dB	40
TV 47-862MHz	dB	34
SAT 950-1750MHz	dB	27
SAT 1750-2150MHz	dB	24
SAT 2150-2400MHz	dB	24

Specifications		
Tap loss	dB	10
Dimensions and packaging		
Pieces		10
EAN code		8016978007523
Multiple EAN		8016978007530
Packaging dimensions	mm	150 x 105 x 50
Product dimensions	mm	41 x 35 x 25
Packaging weight	kg	0.57