

SPTR2

Taps and splitters



2-output "top-down" horizontal splitter with F connector for TV and Satellite band (5-2400MHz).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the outputs and the input.**

SPTR2		
Code		287305
Outputs		2
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	3.5
TV 47-862MHz	dB	4
SAT 950-1750MHz	dB	4
SAT 1750-2150MHz	dB	5
SAT 2150-2400MHz	dB	5.5
Outputs Isolation		
RC 5-40MHz	dB	27.5
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	18
SAT 2150-2400MHz	dB	18

Dimensions and packaging		
Pieces		10
EAN code		8016978094813
Multiple EAN		8016978094820
Packaging dimensions	mm	114 x 128 x 65
Product dimensions	mm	58 x 52 x 25
Packaging weight	kg	0.074
Net Weight	kg	0.75
Weight	kg	0.75