

SPTR3

Taps and splitters

3-output "top-down" horizontal splitter with F connector for TV and Satellite band (5-2400MHz).



Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the outputs and the input.**

SPTR3		
Code		287307
Outputs		3
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	6
TV 47-862MHz	dB	7
SAT 950-1750MHz	dB	7
SAT 1750-2150MHz	dB	9
SAT 2150-2400MHz	dB	9.5
Outputs Isolation		
RC 5-40MHz	dB	25
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	18

Dimensions and packaging		
Pieces		10
EAN code		8016978094868
Multiple EAN		8016978094875
Packaging dimensions	mm	114 x 128 x 65
Product dimensions	mm	58 x 52 x 25
Packaging weight	kg	0.075
Net Weight	kg	0.785
Weight	kg	0.785