

SPTR8

Taps and splitters

8-output "top-down" horizontal splitter with F connector for TV and Satellite band (5-2400MHz).



Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the outputs and the input.**

| SPTR8 | | |
|-------------------|----------|--------|
| Code | | 287309 |
| Outputs | | 8 |
| Impedence | Ω | 75 |
| Insertion loss | | |
| RC 5-40MHz | dB | 11 |
| TV 47-862MHz | dB | 12.5 |
| SAT 950-1750MHz | dB | 12.5 |
| SAT 1750-2150MHz | dB | 15.5 |
| SAT 2150-2400MHz | dB | 16 |
| Outputs Isolation | | |
| RC 5-40MHz | dB | 27.5 |
| TV 47-862MHz | dB | 25 |
| SAT 950-1750MHz | dB | 25 |
| SAT 1750-2150MHz | dB | 25 |
| SAT 2150-2400MHz | dB | 25 |

| Dimensions and packaging | | |
|--------------------------|----|----------------|
| Pieces | | 10 |
| EAN code | | 8016978094905 |
| Multiple EAN | | 8016978094912 |
| Packaging dimensions | mm | 255 x 122 x 65 |
| Product dimensions | mm | 120 x 60 x 22 |
| Packaging weight | kg | 0.136 |
| Net Weight | kg | 1.415 |
| Weight | kg | 1.415 |