

TAPS120

Taps and splitters

1-output "top-down" horizontal tap with 20dB attenuation and F connector for TV and Satellite band (5-2400MHz).



Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS120		
Code		287312
Taps		1
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	1
TV 47-862MHz	dB	1
SAT 950-1750MHz	dB	1.5
SAT 1750-2150MHz	dB	2
SAT 2150-2400MHz	dB	2.5
Tap loss		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	20

Outputs Isolation		
RC 5-40MHz	dB	39
TV 47-862MHz	dB	29
SAT 950-1750MHz	dB	25
SAT 1750-2150MHz	dB	25
SAT 2150-2400MHz	dB	25
Specifications		
Tap loss	dB	20
Dimensions and packaging		
Pieces		1
EAN code		8016978094943
Packaging dimensions	mm	55 x 64 x 27
Product dimensions	mm	55 x 64 x 27
Packaging weight	kg	0.082