


## TAPS412

### Taps and splitters

4-output "top-down" horizontal tap with 12dB attenuation and F connector for TV and Satellite band (5-2400MHz).



### Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS412		
Code		287316
Taps		4
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	2.5
TV 47-862MHz	dB	3
SAT 950-1750MHz	dB	3
SAT 1750-2150MHz	dB	3.5
SAT 2150-2400MHz	dB	4
Tap loss		
RC 5-40MHz	dB	12
TV 47-862MHz	dB	12
SAT 950-1750MHz	dB	12
SAT 1750-2150MHz	dB	12
SAT 2150-2400MHz	dB	12

Outputs Isolation		
RC 5-40MHz	dB	28
TV 47-862MHz	dB	24
SAT 950-1750MHz	dB	23
SAT 1750-2150MHz	dB	22
SAT 2150-2400MHz	dB	22
Specifications		
Tap loss	dB	12
Dimensions and packaging		
Pieces		1
EAN code		8016978094981
Packaging dimensions	mm	85 x 60 x 30
Product dimensions	mm	84 x 64 x 27
Packaging weight	kg	0.106