

TAPS420

Taps and splitters



4-output "top-down" horizontal tap with 20dB attenuation and F connector for TV and Satellite band (**5-2400MHz**).

Technical Chars

- The elegant and compact design allows installation in any junction box.
- The **die-cast zinc** products in this series ensure high performance, with very low insertion losses even at SAT frequencies and high isolation between outputs.
- Prepared for earth connection and wall mounting.
- **DC is allowed to pass between the through output and input.**

TAPS420		
Code		287318
Taps		4
Impedence	Ω	75
Insertion loss		
RC 5-40MHz	dB	2
TV 47-862MHz	dB	2
SAT 950-1750MHz	dB	2
SAT 1750-2150MHz	dB	3
SAT 2150-2400MHz	dB	3.5
Tap loss		
RC 5-40MHz	dB	20
TV 47-862MHz	dB	20
SAT 950-1750MHz	dB	20
SAT 1750-2150MHz	dB	20
SAT 2150-2400MHz	dB	20

Outputs Isolation		
RC 5-40MHz	dB	33
TV 47-862MHz	dB	28
SAT 950-1750MHz	dB	26
SAT 1750-2150MHz	dB	24
SAT 2150-2400MHz	dB	23
Specifications		
Tap loss	dB	20
Dimensions and packaging		
Pieces		1
EAN code		8016978095001
Packaging dimensions	mm	84 x 64 x 27
Product dimensions	mm	84 x 64 x 27
Packaging weight	kg	0.106