

PA₂M

Taps and splitters



2-output clamp splitter of the PAM series in the TV and Satellite band (**5-2400MHz**).

Technical Chars

- Thanks to the **unique retaining clip**, the central connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small dimensions** and the clamp solution, without an F connector, considerably reduce the installation footprint.
- The excellent shielding guarantees the protection of the signal from 5G and 4G LTE disturbances in the air.
- The **new mechanics with protective fins (Rev. 1)** prevent the spring of the central connector from being accidentally pressed while closing the junction boxes.
- DC pass from output to input ports on all the products.

PA2M			
Code		287456	
Outputs		2	
Insertion loss			
RC 5-40MHz	dB	4	
TV 47-862MHz	dB	4.3	
SAT 950-1750MHz	dB	5.1	
SAT 1750-2150MHz	dB	5.8	
SAT 2150-2400MHz	dB	6.8	
Outputs Isolation			
RC 5-40MHz	dB	21	
TV 47-862MHz	dB	21	
SAT 950-1750MHz	dB	21	
SAT 1750-2150MHz	dB	21	
SAT 2150-2400MHz	dB	20	

Data sheet



Dimensions and packaging		
Pieces		10
EAN code		8016978101184
Multiple EAN		8016978101504
Packaging dimensions	mm	132 x 92 x 75
Product dimensions	mm	57 x 35 x 25
Packaging weight	kg	0.065
Net Weight	kg	0.695
Weight	kg	0.695