

PA3M

Taps and splitters

3-output clamp splitter of the PAM series in the TV and Satellite band (5-2400MHz).



Technical Chars

- Thanks to the **unique retaining clip**, the central connector remains integral with the rest of the mechanics, facilitating cable attachment.
- The **very small dimensions** and the clamp solution, without an F connector, considerably reduce the installation footprint.
- The **excellent shielding** guarantees the protection of the signal from **5G and 4G LTE** disturbances in the air.
- The **new mechanics with protective fins (Rev. 1)** prevent the spring of the central connector from being accidentally pressed while closing the junction boxes.
- **DC pass** from output to input ports on all the products.

PA3M		
Code		287457
Outputs		3
Insertion loss		
RC 5-40MHz	dB	6.6
TV 47-862MHz	dB	7.2
SAT 950-1750MHz	dB	8.1
SAT 1750-2150MHz	dB	8.5
SAT 2150-2400MHz	dB	10.5
Outputs Isolation		
RC 5-40MHz	dB	21
TV 47-862MHz	dB	21
SAT 950-1750MHz	dB	21
SAT 1750-2150MHz	dB	21
SAT 2150-2400MHz	dB	20

Dimensions and packaging		
Pieces		10
EAN code		8016978101191
Multiple EAN		8016978101498
Packaging dimensions	mm	132 x 92 x 75
Product dimensions	mm	57 x 35 x 25
Packaging weight	kg	0.066
Net Weight	kg	0.695
Weight	kg	0.695