

GX-4T2CI-BP-00

Galaxia headend



GX-4T2CI-BP-00 receiver module is equipped with one RF coaxial input connector (F Female) and two PCMCIA Common Interface slots. The module is able to tune **up to four DVB-T/T2 digital terrestrial multiplexes**, decrypt the scrambled programs through the C.I. slots and share and pool the contents to the **GALAXIA** main chassis.

Technical Chars

- 1 RF Coaxial Input (**F Female**)
- Tunes up to 4 **DVB-T/T2** digital terrestrial multiplexes
- 2x **PCMCIA Common Interface** Slots capable of decoding programs from any of the 4 tuners on board the module
- **"Hot-swappable"** module
- **On-board WEB interface:** programming of all parameters is easily done via HTML web interface

GX-4T2CI-BP-00		
Code		287641
Input		
Input no.		1 (4 DTT tuners)
Input level	dBμV	30-88
Demodulators		<ul style="list-style-type: none"> • DVB-T: QPSK/16QAM/64QAM • DVB-T2: QPSK/16QAM/64QAM/256QAM
Input band		47-862
FEC		<ul style="list-style-type: none"> • DVB-T: 1/4, 1/8, 1/16, 1/32 • DVB-T2: 1/4, 1/8, 1/16, 1/32, 1/128, 19/256, 19/128
Specifications		
Connectors		1x F-female (RF)
Programming mode		Web interface
Current consumption	W	8
Common interface		2 x PCMCIA (Standard EN50221, TS10169)
Operating temperature	°C	-5 to +50
Conformity		EN50083-2

Dimensions and packaging		
Pieces		1
EAN code		8016978106752
Packaging dimensions	mm	330 x 185 x 80
Product dimensions	mm	270 x 115 x 20
Packaging weight	kg	1.5